

# RITRAMA overlaminates

www.ritrama.com



## PRODUCT CODE: 3-9829

### PRODUCTION DESCRIPTION

Ideal for temporary and short-term durability (6 months). This overlaminate product is an excellent choice for economical floor graphics applications. This product is offered on a film liner for excellent wet out and is UL-410 classified for slip resistance

### APPLICATIONS

- Floor graphics
- Point of purchase displays
- Counter graphics

### FEATURES AND BENEFITS

- UL-410 classified for slip resistance
- Environmentally friendly
- Clear textured

### TECHNICAL DATA

Face Material	3.75-mil polyolefin
Color and Finish	Clear textured
Adhesive	FG, Overlaminating permanent acrylic
Liner	1.2 mil clear film

### TYPICAL CHARACTERISTICS

Target Adhesion Values (PSTC-1, 180° peel @ 12"/min., 73°F, on Stainless Steel)	<u>15 min.</u> 65 oz.	<u>24 hr.</u> 75 oz.
Minimum Application Temperature	50°F	
Service Temperature Range	-40°F to +180°F	
Shelf Life (@ 73°F, 50% RH)	2 years	
Outdoor Durability	Indoor use only	

### CHEMICAL RESISTANCE

Distilled Water (24 hr)	No Effect
Detergent (24 hr)	No Effect
10% HCl (10 min)	No Effect
10% Ammonium Hydroxide (10 min)	No Effect
Gasoline (1 hr)	No Effect



The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.  
Aug-09

Ritrama Inc. Minneapolis, MN  
800 Kasota Ave. S.E.  
Minneapolis, MN 55414  
Toll Free: 1-800-328-5071  
Phone: 612-378-2277  
Fax: 612-378-9327  
Email: info@ritrama.com

Ritrama Inc. Cleveland, OH  
341 Eddy Road  
Cleveland, OH 44108  
Toll Free: 1-800-328-5071  
Phone: 216-851-2300  
Fax: 216-851-1938  
Email: info@ritrama.com

Warehouses: Chino, CA-Orlando, FL-Wichita, KS-Seekonk, MA-Cleveland, OH