



**PRODUCT CODE: 3-7844**  
**RI-2060 UV**

**PRODUCTION DESCRIPTION**

3.5-mil high gloss clear flexible vinyl is an intermediate vinyl overlamine film designed to protect and enhance images and graphics. Product is also designed to inhibit UV light absorption.

**APPLICATIONS**

- Protects and enhances images and graphics

**FEATURES AND BENEFITS**

- Inhibits UV light absorption

**TECHNICAL DATA**

Face Material	3.5-mil flexible vinyl
Color and Finish	Gloss clear
Adhesive	Overlaminating permanent acrylic
Liner	50# bleached glassine

**TYPICAL CHARACTERISTICS**

Average Adhesion Values	<u>15 min.</u>	<u>24 hr.</u>
(PSTC-1, 180° peel @ 12"/min., 73°F, on Stainless Steel)	50 oz.	75 oz.
Minimum Application Temperature	50°F	
Service Temperature Range	-40°F to +180°F	
Shelf Life (@ 73°F, 50% RH)	2 years	
Outdoor Life	3 years	

**CHEMICAL RESISTANCE**

Distilled Water (24 hr)	No Effect
Detergent (24 hr)	No Effect
10% HCl (10 min)	N/A
10% Ammonium Hydroxide (10 min)	No Effect
Anti-Freeze (24 hr)	No Effect
SAE 20 Motor Oil (24 hr)	No Effect

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

Sept. 07

Form 108-01 (1/99)