



PRODUCT CODE: 3-7835
RI-2070 UV

PRODUCT DESCRIPTION

3.5-mil flexible matte-clear vinyl is an intermediate vinyl overlaminate film designed to protect and enhance images and graphics. Product is also designed to inhibit UV light absorption.

APPLICATIONS

- Overlaminates for your digital media

FEATURES AND BENEFITS

- 3.5-mil matte-clear flexible vinyl, overlaminating permanent adhesive, 50# bleached glassine liner.

TECHNICAL DATA

Face Material	3.5-mil flexible vinyl
Color and Finish	Matte clear
Adhesive	Overlaminating permanent acrylic
Liner	50# bleached glassine

TYPICAL CHARACTERISTICS

Average Adhesion Values	<u>15 min.</u>	<u>24 hr.</u>
(PSTC-1, 180° peel @ 12"/min., 73°F, on Stainless Steel)	50 oz.	75 oz.
Minimum Application Temperature	50°F	
Service Temperature Range	-40°F to +180°F	
Shelf Life (@ 73°F, 50% RH)	2 years	
Outdoor Life	3 years	

CHEMICAL RESISTANCE

Distilled Water (24 hr)	No Effect
Detergent (24 hr)	No Effect
10% HCl (10 min)	N/A
10% Ammonium Hydroxide (10 min)	No Effect
Anti-Freeze (24 hr)	No Effect
SAE 20 Motor Oil (24 hr)	No Effect

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

Sept. 07

Form 108-01 (1/99)