



## PRODUCT CODE: 3-9705

### PRODUCT DESCRIPTION

White mounting film designed for laminating permanently to printed substrates.

### APPLICATIONS

- Adhering nameplates and backlit panels
- Point of purchase displays
- Promotional products
- Temporary graphics

### FEATURES AND BENEFITS

- Permanent acrylic on both sides with high peel and good tack.

### TECHNICAL DATA

Face Material	2.3-mil polypropylene
Color and Finish	White
Adhesive	Permanent acrylic each side
Liner	60# bleached kraft

### TYPICAL CHARACTERISTICS

Target Adhesion Values (PSTC-1, 180° peel @ 12"/min., 73°F, on Stainless Steel)	<u>15 min.</u> 35 oz.	<u>24 hr.</u> 45 oz.
Static Shear (1/2-inch x 1/2-inch x 500 grams)	> 24 hours	
Service Temperature Range	-40°F to +180°F	
Shelf Life (@ 73°F, 50% RH)	2 years	
Outdoor Durability	2 years	

### CHEMICAL RESISTANCE

Distilled Water (24 hr)	No Effect
Detergent (24 hr)	No Effect
10% HCl (10 min)	No Effect
10% Ammonium Hydroxide (10 min)	No Effect
Anti-Freeze (24 hr)	No Effect
SAE 20 Motor Oil (24 hr)	No Effect
Gasoline (1 hr)	No Effect

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

Oct-09

Form 108-01(1/99)