



PRODUCT CODE: 3-8621

PRODUCTION DESCRIPTION

Ideal for long-term durability, this overlaminate product is an excellent choice for high volume and extended floor graphics applications. This product is offered on a film liner for excellent wet out and is UL-410 approved for slip resistance.

APPLICATIONS

- Floor graphics
- Counter graphics

FEATURES AND BENEFITS

- UL-Recognized product: file number MH14249.
- 5.0-mil clear scuff and slip resistant vinyl.

TECHNICAL DATA

Face Material	5.0-mil vinyl
Color and Finish	Slip resistant clear
Adhesive	FG, Permanent acrylic
Liner	1.2-mil polyester

TYPICAL CHARACTERISTICS

Target Adhesion Values (PSTC-1, 180° peel @ 12"/min., 73°F, on Stainless Steel)	<u>15 min.</u> 140 oz.	<u>24 hr.</u> 165 oz.
Minimum Application Temperature	50°F	
Service Temperature Range	-40°F to +180°F	
Shelf Life (@ 73°F, 50% RH)	2 years	
Outdoor Life	30 days	
Flammability	Self-Extinguishing	

CHEMICAL RESISTANCE

Distilled Water (24 hr)	No Effect
Detergent (24 hr)	No Effect
10% HCl (10 min)	N/A
10% Ammonium Hydroxide (10 min)	No Effect
Gasoline (1 hr)	No Effect



The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.
Aug-09